


AL600ULX Series

Power Supply/Chargers

Altronix AL600ULX series power supply/chargers convert a 115VAC, 60Hz input into a single fused, four (4), eight (8) or sixteen (16) fuse or PTC protected outputs. Outputs are selectable for 12VDC or 24VDC with a total of 6A max.



AL600ULPD8

Key Features

- Available with 1, 4, 8 or 16 outputs
- Fused or PTC protected outputs
- Supervision:
 - AC Fail.
 - Battery Fail and Battery Presence
- Built-in charger for sealed lead acid or gel type batteries
- Instantaneous transfer to stand-by batteries
- Short circuit and overload protection
- AC input and DC output options
- UL Listed in the U.S. and Canada
- CSFM and MEA Approved
- Lifetime Warranty
- All units are available in grey or red enclosure

AL600ULX Series Power Supply Configuration Reference Chart

Altronix Model Number	Total Output Rating (A)	Input Rating: 115VAC, 60Hz	Input Fuse Rating	Power Distribution Module	Class 2 Rated Power-Limited Outputs (auto-resettable)	Number of Outputs	Fused Output Ratings	PTC Output Ratings	Accommodates Batteries
AL600ULX	6A	3.5A	5A/250V	N/A	-	1	6A	-	Two (2) 7AH
AL600ULXX				-	1	6A	-	Two (2) 12AH	
AL600ULPD4				PD4UL	-	4	3.5A	-	Two (2) 7AH
AL600ULPD4CB				PD4ULCB	✓	4	-	2.5A	Two (2) 7AH
AL600ULPD8				PD8UL	-	8	3.5A	-	Two (2) 7AH
AL600ULPD8CB				PD8ULCB	✓	8	-	2.5A	Two (2) 7AH
AL600ULXPD16				Two (2) PD8UL	-	16	3.5A	-	Two (2) 12AH
AL600ULXPD16CB				Two (2) PD8ULCB	✓	16	-	2.5A	Two (2) 12AH

Lifetime Warranty



AL600ULX Series

Power Supply/Chargers

Specifications

Input

Voltage 115VAC, 60Hz, 3.5A max.
Fusing 5A / 250V

Outputs

Voltage 12VDC or 24VDC selectable
Current 6A @ 12VDC or 24VDC continuous max.
Protection Fused 3.5A / PTC 2.5A
Other Overvoltage protection
Filtered and regulated

Back-up Battery *(not included)*

Capacity 7AH / 12VDC (1 or 2 within enclosure)
12AH / 12VDC (requires larger "X" enclosure)
40 AH / 65 AH (requires separate enclosure)

Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous

Supervision

AC Failure Form "C" contacts
Battery Form "C" contacts

Indicators (LED)

Input 115VAC is present
DC Output Powered
Battery Discharged or not connected

Agency Listings

All Models:

UL:
UL294 Access Control System Units
UL1481 Power Supplies for
Fire Protective Signaling Systems

cUL:

CSA C22.2 No.205 Signal Equipment

AL600ULX and AL600ULXX only:

CSFM California State Fire Marshall Approved
MEA NYC Department of Buildings Approved
FM Factory Mutual Approved

Physical and Environmental

Dimensions (H x W x D)

AL600ULX, AL600ULPD4(CB), AL600ULPD8(CB):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)
AL600ULXX, AL600ULXPD16(CB):
15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)

Product / Shipping Weight (approx.)

Model	Product Weight	Shipping Weight
AL600ULX	7.05 lbs. (3.2 kg)	8.9 lbs. (4.1 kg)
AL600ULXX	8.65 lbs. (3.92 kg)	10.95 lbs. (4.97 kg)
AL600ULPD4(CB)	7.2 lbs. (3.27 kg)	9.05 lbs (4.1 kg)
AL600ULPD8(CB)	7.3 lbs. (3.31 kg)	9.15 lbs (4.15 kg)
AL600ULXPD16(CB)	8.95 lbs. (4.06 kg)	11.25 lbs. (5.1 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)
Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.):

12VDC: 37 BTU/Hr.
24VDC: 74 BTU/Hr.

Lifetime Warranty